and 453/2010



ARTISTRI[™] P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

This Safety Data Sheet adheres to the standards and regulatory requirements of Great Britain and may not meet the regulatory requirements in other countries.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : ARTISTRI[™] P5100+ CYAN PIGMENT INK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Printing ink

1.3. Details of the supplier of the safety data sheet

Company : Du Pont de Nemours (Deutschland) GmbH

Hugenottenallee 175 D-63263 Neu-Isenburg

Germany

Telephone : +49 (0) 6102 18-0

Telefax : +49 (0) 6102 18-1224

E-mail address : sds-support@che.dupont.com

1.4. Emergency telephone number

Emergency telephone number : +(44)-870-8200418

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Specific target organ toxicity -

repeated exposure, Category

2

Chronic aquatic toxicity,

Category 3

H373: May cause damage to organs through prolonged or repeated exposure.

H412: Harmful to aquatic life with long lasting effects.

Harmful R48/22: Harmful: danger of serious damage to health by prolonged exposure if

swallowed.

Dangerous for the R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in

environment the aquatic environment.

2.2. Label elements

and 453/2010



ARTISTRI™ P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491



Warning

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Special labelling of certain The following percentage of the mixture consists of ingredient(s) with unknown

substances and mixtures acute oral toxicity:, 8.6437 %

The following percentage of the mixture consists of ingredient(s) with unknown

acute dermal toxicity:, 8.6437 %

The following percentage of the mixture consists of ingredient(s) with unknown

acute inhalation toxicity:, 8.6437 %

The following percentage of the mixture consists of ingredient(s) with unknown

hazards to the aquatic environment:, 8.6437 %

Contains: 1,2-Benzisothiazol-3(2H)-one / EUH208: May produce an allergic

reaction.,

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P273 Avoid release to the environment.

P314 Get medical advice/ attention if you feel unwell.

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3. Other hazards

May cause eye and skin irritation.

Inhalation may cause central nervous system effects.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

0.2			
Registration number Classification		Classification according to	Concentration
	according to	Regulation (EU) 1272/2008	(% w/w)
	Directive 67/548/EEC	(CLP)	

Ethane-1,2-diol (CAS-No.107-21-1) (EC-No.203-473-3)

Xn;R22 R48/22 R67	Acute Tox. 4; H302 STOT SE 3; H336 STOT RE 2; H373	>= 10 - < 15 %
-------------------------	--	----------------

and 453/2010



ARTISTRI™ P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

2,2'-Oxydiethanol (CAS-No.111-46-6) (EC-No.203-872-2)

Xn;R22	Acute Tox. 4; H302	>= 1 - < 10 %

2-Pyrrolidone (CAS-No.616-45-5) (EC-No.210-483-1)

2 · j · · · · · · · · · · · · · · · · ·					
		Xi;R36	Eye Irrit. 2; H319	>= 1 - < 3 %	
			-		

1,2-Benzisothiazol-3(2H)-one (CAS-No.2634-33-5) (EC-No.220-120-9)

(M-Factor: 10[Acute] 10[Chronic])

	Xn;R22	Acute Tox. 4; H302	>= 0.025 - < 0.05 %		
	Xi;R38	Skin Irrit. 2; H315			
	R41	Eye Dam. 1; H318			
	R43	Skin Sens. 1; H317			
	N;R50/53	Aquatic Acute 1; H400			
		Aquatic Chronic 1; H410			
		·			

The above products are compliant to REACH registration obligations; Registration number(s) may not be provided because substance(s) are exempted, not yet registered under REACH or are registered under another regulatory process (biocide uses, plant protection products), etc.

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice : Never give anything by mouth to an unconscious person. When symptoms

persist or in all cases of doubt seek medical advice.

Inhalation : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If breathing

is irregular or stopped, administer artificial respiration. Get medical attention.

Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15

minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before

re-use.

Eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty

of water, also under the eyelids, for at least 15 minutes. Get medical advice/

attention.

Ingestion : If swallowed, call a poison control centre or doctor immediately. Rinse mouth

with water. DO NOT induce vomiting unless directed to do so by a physician or

poison control center.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:, Irritation, Cough

and 453/2010



ARTISTRI™ P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

Effects of breathing high concentrations of vapour may include:, Drowsiness, Dizziness

Skin contact may provoke the following symptoms:, Irritation with discomfort or pain, redness or rash, itching or swelling., Allergic reactions

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Eye contact may provoke the following symptoms:, Irritation, Pain, tearing, swelling, redness, or temporary visual impairment.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment : No specific intervention is indicated. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

: Water spray, Dry chemical, Carbon dioxide (CO2)

5.2. Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Hazardous decomposition products formed under fire conditions. (see also

section 10) Avoid breathing decomposition products.

5.3. Advice for firefighters

Special protective equipment

for firefighters

: Exposure to decomposition products may be a hazard to health. Wear self-

contained breathing apparatus for firefighting if necessary.

Further information : Evacuate personnel to safe areas. Stop spill/release if it can be done with

minimal risk. Do not allow run-off from fire fighting to enter drains or water

courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Wear

suitable protective equipment.

6.2. Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so. Prevent product from

entering drains. Clean contaminated floors and objects thoroughly while

observing environmental regulations.

and 453/2010



ARTISTRI™ P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spill. Soak up with inert absorbent material. Collect and contain

contaminated absorbent and dike material for disposal. Keep in suitable, closed containers for disposal. Ventilate the area. Clean contaminated floors and

objects thoroughly while observing environmental regulations.

Other information : Dispose of in accordance with local regulations.

6.4. Reference to other sections

For personal protection see section 8. For disposal instructions see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling : Avoid inhalation, ingestion and contact with skin and eyes. Do not use in areas

without adequate ventilation. For personal protection see section 8.

Advice on protection against fire and explosion

: Normal measures for preventive fire protection.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep containers tightly closed in a cool, well-ventilated place. Do not store or consume food, drink or tobacco in areas where they may become contaminated

with this material. Do not reuse empty container.

Other data : Stable under normal conditions.

7.3. Specific end use(s)

no data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

If sub-section is empty then no values are applicable.

Components with workplace control parameters

Туре	Control	Update	Basis	Remarks
Form of exposure	parameters			

Ethane-1,2-diol (CAS-No. 107-21-1)

and 453/2010



ARTISTRI™ P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

TWA Vapor.	52 mg/m3 20 ppm	2007	EH40 WEL	
STEL Vapor.	104 mg/m3 40 ppm	2007	EH40 WEL	
SKIN_DES Vapor.		2007	EH40 WEL	Can be absorbed through skin.
SKIN_DES Particulate.		2007	EH40 WEL	Can be absorbed through skin.
TWA Particulate.	10 mg/m3	2007	EH40 WEL	
TWA	52 mg/m3 20 ppm	12 2009	EU ELV	Indicative
STEL	104 mg/m3 40 ppm	12 2009	EU ELV	Indicative
SKIN_DES		12 2009	EU ELV	Can be absorbed through skin.

2,2'-Oxydiethanol (CAS-No. 111-46-6)

	- 1			
T	WA	101 mg/m3	2007	EH40 WEL
		23 ppm		

Derived No Effect Level (DNEL)

Ethane-1,2-diol : Type of Application (Use): Workers

Exposure routes: Inhalation

Health Effect: Systemic effects, Long-term exposure

Value: 35 mg/m3

: Type of Application (Use): Workers Exposure routes: Skin contact

Health Effect: Systemic effects, Long-term exposure

Value: 106 mg/kg body weight (bw) /day

Predicted No Effect Concentration (PNEC)

Ethane-1,2-diol : Value: 10 mg/l

Compartment: Fresh water

: Value: 1 mg/l

Compartment: Marine water

: Value: 10 mg/l Compartment: Water

Remarks: Intermittent use/release

: Value: 20.9 mg/kg dry weight (d.w.) Compartment: Fresh water sediment

and 453/2010



ARTISTRI[™] P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

: Value: 1 mg/kg dry weight (d.w.) Compartment: Marine sediment

: Value: 1.53 mg/kg dry weight (d.w.)

Compartment: Soil

: Value: 199.5 mg/l

Compartment: Sewage treatment plants

8.2. Exposure controls

Engineering measures : Ensure adequate ventilation. Maintain air concentrations below occupational

exposure standards. General mechanical ventilation is normally adequate but use local exhaust where necessary to maintain exposures below acceptable

limits.

Eye protection : Wear safety glasses or coverall chemical splash goggles.

Hand protection : Material: Protective gloves complying with EN 374.

Gloves must be inspected prior to use. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC

and the standard EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount

of dangerous substances, and to the specific work-place. Lightweight protective

clothing and safety shoes are recommended.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Avoid

contact with skin, eyes and clothing. Use with adequate ventilation. Keep container closed. Keep away from food and drink. Wash hands before eating, drinking, or smoking. Remove contaminated clothing and protective equipment before entering eating areas. Wash contaminated clothing before re-use.

Respiratory protection : No personal respiratory protective equipment normally required. When workers

are facing concentrations above the exposure limit they must use appropriate certified respirators. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use

limitations specified by the manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form : liquid

7/16

and 453/2010



ARTISTRI™ P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

Colour : blue

Odour : not significant

pH : 7-9

Boiling point : 100 °C

Flash point : 93 °C

Evaporation rate : Slower than Ether

9.2. Other information

Phys.-chem./other information : No other data to be specially mentioned.

SECTION 10: Stability and reactivity

10.1. Reactivity : No dangerous reaction known under conditions of normal use.

10.2. Chemical stability : The product is chemically stable under recommended conditions of storage, use

and temperature.

10.3. Possibility of: None reasonably foreseeable. Stable at normal temperatures and storage

hazardous reactions conditions.

10.4. Conditions to avoid : Avoid extreme heat. Do not freeze.

10.5. Incompatible materials : Acids, bases and strong oxidizing agents

10.6. Hazardous : Under fire conditions: decomposition products : Under fire conditions:

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity

Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Ethane-1,2-diol

LD50 / Cat: 1,650 mg/kg

• 2,2'-Oxydiethanol

Acute toxicity estimate: 500 mg/kg

2-Pyrrolidone

LD50 / Rat: 8,000 mg/kg

Method: OECD Test Guideline 401

and 453/2010



ARTISTRI[™] P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

1,2-Benzisothiazol-3(2H)-one LD50 / Rat: 670 mg/kg

Acute inhalation toxicity

- Ethane-1,2-diol no data available
- 2,2'-Oxydiethanol
 Acute toxicity estimate / 4 h Rat : > 5 mg/l
- 2-Pyrrolidone LC50 / 4 h Rat

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

Acute dermal toxicity

Ethane-1,2-diol
 LD50 / Mouse : > 3,500 mg/kg

• 2,2'-Oxydiethanol

LD50 / Rabbit : 13,300 mg/kg

• 2-Pyrrolidone

LD50 / Rat : > 2,000 mg/kg Method: OECD Test Guideline 402

 1,2-Benzisothiazol-3(2H)-one LD50 / Rabbit : > 2,000 mg/kg

Skin irritation

Ethane-1,2-diol

Rabbit

Classification: Not classified as irritant

Result: No skin irritation

• 2,2'-Oxydiethanol

Rabbit

Classification: Not classified as irritant

Result: slight irritation

• 2-Pyrrolidone

Rabbit

Classification: Not classified as irritant

Result: No skin irritation

Method: OECD Test Guideline 404

• 1,2-Benzisothiazol-3(2H)-one

Rabbit

Classification: Irritating to skin.

and 453/2010



ARTISTRI™ P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

Result: Skin irritation

Information given is based on data obtained from similar substances.

Eye irritation

• Ethane-1,2-diol

Rabbit

Classification: Not classified as irritant

Result: No eye irritation

2,2'-Oxydiethanol

Rabbit

Classification: Not classified as irritant

Result: slight irritation

2-Pyrrolidone

Rabbit

Classification: Irritating to eyes.

Result: Eye irritation

• 1,2-Benzisothiazol-3(2H)-one

Rabbit

Classification: Risk of serious damage to eyes.

Result: Severe eye irritation

Information given is based on data obtained from similar substances.

Sensitisation

• Ethane-1,2-diol

human

Classification: Does not cause skin sensitisation.

Result: Does not cause skin sensitisation.

• 2,2'-Oxydiethanol

Guinea pig

Classification: Not a skin sensitizer.

Result: Did not cause sensitisation on laboratory animals.

humar

Classification: Not a sensitizer by inhalation.

Result: Patch test on human volunteers did not demonstrate sensitisation properties.

• 2-Pyrrolidone

Mouse

Classification: Does not cause skin sensitisation.

Result: Does not cause skin sensitisation.

Method: OECD Test Guideline 429

Information given is based on data obtained from similar substances.

• 1,2-Benzisothiazol-3(2H)-one

Mouse Local lymph node test

Classification: May cause sensitisation by skin contact.

Result: Causes sensitisation.

and 453/2010



ARTISTRI™ P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

human

Classification: May cause sensitisation by skin contact.

Result: Positive in human patch test.

Repeated dose toxicity

• Ethane-1,2-diol

Oral Rat

Kidney damage

• 2-Pyrrolidone

Oral Rat

NOAEL: 207 mg/kg

Method: OECD Test Guideline 408

Kidney effects

• 1,2-Benzisothiazol-3(2H)-one

Oral Rat

No toxicologically significant effects were found.

Mutagenicity assessment

• Ethane-1,2-diol

Animal testing did not show any mutagenic effects. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

• 2,2'-Oxydiethanol

Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Animal testing did not show any mutagenic effects.

2-Pyrrolidone

Animal testing did not show any mutagenic effects. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

1,2-Benzisothiazol-3(2H)-one

Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Animal testing did not show any mutagenic effects.

Carcinogenicity assessment

Ethane-1,2-diol

Not classifiable as a human carcinogen. Animal testing did not show any carcinogenic effects.

2,2'-Oxydiethanol

Not classifiable as a human carcinogen.

Toxicity to reproduction assessment

• Ethane-1,2-diol

No toxicity to reproduction No effects on or via lactation Animal testing showed no reproductive toxicity.

• 2,2'-Oxydiethanol

and 453/2010



ARTISTRI™ P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

No toxicity to reproduction Animal testing showed no reproductive toxicity.

• 2-Pyrrolidone

No toxicity to reproduction Animal testing showed no reproductive toxicity.

• 1,2-Benzisothiazol-3(2H)-one

No toxicity to reproduction Animal testing showed effects on reproduction at levels equal to or above those causing parental toxicity.

Assessment teratogenicity

• Ethane-1,2-diol

Evidence suggests the substance is not a developmental toxin in animals.

2,2'-Oxydiethanol

Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.

• 2-Pyrrolidone

Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.

• 1,2-Benzisothiazol-3(2H)-one

Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.

Further information

No data is available on the product itself. Information given is based on data on the components.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity to fish

• Ethane-1,2-diol

LC50 / 96 h / Pimephales promelas (fathead minnow): 72,860 mg/l

• 2,2'-Oxydiethanol

LC50 / 96 h / Pimephales promelas (fathead minnow): 75,200 mg/l

LC50 / 48 h / Leuciscus idus (Golden orfe): > 10,000 mg/l

1,2-Benzisothiazol-3(2H)-one

LC50 / 96 h / Oncorhynchus mykiss (rainbow trout): 1.6 mg/l

Toxicity to aquatic plants

• Ethane-1,2-diol

ErC50 / 96 h / Pseudokirchneriella subcapitata (green algae): 6,500 mg/l

and 453/2010



ARTISTRI™ P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

2-Pyrrolidone
 ErC50 / 72 h / Desmodesmus subspicatus (green algae): > 500 mg/l

 1,2-Benzisothiazol-3(2H)-one EC50 / 72 h / Algae: 0.15 mg/l

Toxicity to aquatic invertebrates

Ethane-1,2-diol
 EC50 / 48 h / Daphnia magna (Water flea): > 100 mg/l
 Method: OECD Test Guideline 202

2,2'-Oxydiethanol
 EC50 / 24 h / Daphnia magna (Water flea): > 10,000 mg/l

2-Pyrrolidone
 EC50 / 48 h / Daphnia magna (Water flea): > 500 mg/l
 Method: Directive 67/548/EEC, Annex V, C.2.

1,2-Benzisothiazol-3(2H)-one
 EC50 / 48 h / Aquatic invertebrates: 0.047 mg/l

12.2. Persistence and degradability

Biodegradability

Ethane-1,2-diol
 / 10 d
 Biodegradation: 90 - 100 %
 Method: OECD Test Guideline 301
 Readily biodegradable

2,2'-Oxydiethanol / 28 d Biodegradation: 90 %

Readily biodegradable

 2-Pyrrolidone Biodegradable Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

 Ethane-1,2-diol Bioaccumulation is unlikely.

2,2'-Oxydiethanol
 Bioconcentration factor (BCF): 10 - 180
 Bioaccumulation is unlikely.

• 2-Pyrrolidone

and 453/2010



ARTISTRI™ P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

Bioaccumulation is unlikely.

 1,2-Benzisothiazol-3(2H)-one Bioaccumulation is unlikely.

12.4. Mobility in soil

no data available

12.5. Results of PBT and vPvB assessment

no data available

12.6. Other adverse effects

Additional ecological information

No data is available on the product itself. Information given is based on data on the components.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : Dispose of in accordance with the European Directives on waste and hazardous

waste. Never place unused product down any indoor or out door drain.

Contaminated packaging : Do not reuse empty container. Contaminated/not cleaned containers should be

treated/handled like product waste. Dispose of container properly. Refer to applicable Local, State/Provincial, and Federal Regulations, as well as industry

Standards.

SECTION 14: Transport information

ADR

14.1. UN number: Not applicable
14.2. UN proper shipping name: Not applicable
14.3. Transport hazard class(es): Not applicable
14.4. Packing group: Not applicable

14.5. Environmental hazards: none

14.6. Special precautions for user:

Not classified as dangerous in the meaning of transport regulations.

IATA_C

14.1. UN number: Not applicable
14.2. UN proper shipping name: Not applicable
14.3. Transport hazard class(es): Not applicable
14.4. Packing group: Not applicable

14.5. Environmental hazards: none

14.6. Special precautions for user:

Not classified as dangerous in the meaning of transport regulations.

IMDG

14.1. UN number: Not applicable14.2. UN proper shipping name: Not applicable

14/16

and 453/2010



ARTISTRI[™] P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

14.3. Transport hazard class(es): Not applicable14.4. Packing group: Not applicable

14.5. Environmental hazards: none

14.6. Special precautions for user:

Not classified as dangerous in the meaning of transport regulations.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : Take note of Directive 98/24/EC on the protection of the health and safety of

workers from the risks related to chemical agents at work.

Take note of Dir 92/85/EEC on the safety and health at work of pregnant

workers

Take note of Dir 94/33/EC on the protection of young people at work.

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Text of R-phrases mentioned in Section 3

R22 Harmful if swallowed.
R36 Irritating to eyes.
R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R67 Vapours may cause drowsiness and dizziness.

Full text of H-Statements referred to under section 3.

H302	Harmful if swallowed.
H315	Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADR European Agreement concerning the International Carriage of Dangerous Goods by

and 453/2010



ARTISTRI™ P5100+ CYAN PIGMENT INK

Version 3.0 (replaces: Version 2.0)

Revision Date 26.04.2015 Ref. 130000128491

Road

ATE Acute toxicity estimate

CAS-No. Chemical Abstracts Service number CLP Classification, Labelling and Packaging

EbC50 Concentration at which 50% reduction of biomass is observed

EC50 Median effective concentration

EN European Norm

EPA Environmental Protection Agency

ErC50 Concentration at which a 50% inhibition of growth rate is observed

EyC50 Concentration at which 50 % inhibition of yield is observed

IATA_C International Air Transport Association (Cargo)

IBC International Bulk Chemical Code
ICAO International Civil Aviation Organization
ISO International Standard Organization
IMDG International Maritime Dangerous Goods

LC50 Median Lethal Concentration

LD50 Median Lethal Dose

LOEC Lowest Observed Effect Concentration

LOEL Lowest observed effect level

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.o.s. Not Otherwise Specified

NOAEC No Observed Adverse Effect Concentration

NOAEL No observed adverse effect level NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

OECD Organisation for Economic Co-operation and Development OPPTS Office of Prevention, Pesticides and Toxic Substances

PBT Persistent, Bioaccumulative and Toxic

STEL Short term exposure limit
TWA Time Weighted Average (TWA):

vPvB very Persistent and very Bioaccumulative

Further information

The DuPont Oval Logo is a registered trademark of E.I. du Pont de Nemours and Company.

Significant change from previous version is denoted with a double bar.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.