Technical datasheet

Printable self adhesive vinyl: HK106

1. Product description:

HK106 is a middle time outdoor durability self adhesive vinyl, it is comprised of a glossy white monomeric vinyl face sheet with transparent permanent adhesive and a release paper.

• Advantage

- ✓ 100micron glossy vinyl surface
- ✓ 2years outdoor life
- ✓ Suitable for Solvent/ECO digital printing, compatible for UV, latex ink
- ✓ Excellent ability for uneven and arched surface
- ✓ Soft stretchable film with strong adhesive, suitable for indented surface

• Specification:

Vinyl thickness	Liner	Width	Length
100 micron	140g/m2 paper	0.914/1.07/1.27/1.37/1.52m	50m

2. Use area

- ✓ Body of car, truck, bus, van wraps
- ✓ Flat wall body
- ✓ Other flat paint, plastic, metal, acrylic board surface

3. Limitation

NOT recommended for the following applications:

- \checkmark The surfaces of substrates are dirty, solvent cleaned, grease, silicon coating which affect the adhesion of the glue.
- arreet the adhesion of the grae.
- ✓ Lacquered or painted surfaces freshly

4. Temperature ranges

Minimum operating temperature: >9°C

Service temperature range: -25° C to~ 70°C

5. Shelf life:

1 year in material's original packaging, storage temperature of 15-22 deg C, relative Page 1 of 2 humidity of $50 \sim 55\%$

6. Durability:

2 years service life. Correct substrate preparation and maintenance of vinyl will enhance durability.

7. Technical data

connou	uutu		
Film	Composition	Glossy calendered monomeric vinyl	
	Thickness	100±5 um GB/T6672-2001	
	Dimensional Stability	Max 0.5mm (48 hours at 70°C, Aluminium	
	Dimensional Stability	plate, MD) FTM14	
	Seawater resistance	100h/23°C no variation (adhered to aluminium	
	Seawater resistance	plate) DIN50021	
Adhesive	Adhesive Type	Clear solvent, pressure sensitive	
	Removable ability	Permanent	
	Net weight	20±1 g/m2	
	Initial Adhesion(2hrs)	1.0±0.1kgf/inch FTM9	
	180°Peel strength(steel, 24hrs)	2.0±0.2kgf/inch FTM1	
Liner	Type Single PE coating silicon art paper		
	Weight	140±5 g/m2	
	Release force	40g	
	SA rate	>85%	

Notice: The purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All published document is based on our R &D center careful research and test work.