

AIR FIX 1

It is cold fixing agent



Highlights

- It is an additive used to improve the dry-wet rubbing and washing fastness properties of water based products
- (1-1,5)% could be added to improve washing fastness of all Hybrid Inks and Discharge Inks
- 3% Should be added into Flock Adhesive Flock Applications
- (1,5-2)% Could be added in Antifoil applications into all whites and clear bases
- 1,5% Could be added into TB White and TB Clear Base for self curing applications
- Recommended Percentage: (0,3-3)%



Printing Tips

- It has been manufactured to improve washing fastness



Precautions

- Before usage, please stir the product well. Do not use any additives that are not advised.
- It makes crosslink at thermal applications and under room temperature.
- The mixture should be consumed within 24 hours after Air Fix 1 is added into the water based printing bases. Otherwise, it can damage the mixture.
- It is packed in 6kg cans.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

Shipping & Storage

41°F - 86°F (5°C - 30°C)



Health & Safety

Please see: Safety Data Sheet

