

POLI-TAPE



HEAT
TRANSFER
VINYLs



POLI-FLEX® TURBO

STANDARD

4901 WHITE 4901-1 WHITE*



NEW

4955 VIOLET



NEW

4952 FROG GREEN



4902 BLACK 4902-1 BLACK*



4961 BABY PINK



4968 AQUA GREEN



4917 BEIGE



NEW

4953 LIGHT BERRY



4977 MINT



4954 SAND BEIGE



NEW

4962 FUCHSIA



4916 BROWN



4958 PASTEL YELLOW



NEW

4909 BORDEAUX



4912 GREY



4919 LEMON YELLOW



4914 PURPLE



NEW

4951 LIGHT GREY



4918 MEDIUM YELLOW



4965 SKY BLUE



4910 YELLOW



4906 ROYAL BLUE



4915 ORANGE



NEW

4979 CLASSIC BLUE



4973 FLAME RED



4905 NAVY BLUE



4908 RED



4967 APPLE GREEN



4929 CORAL



4904 GREEN



METALLIC

4920 GOLD METALLIC



4930 SILVER METALLIC



NEW

4956 BRONZE



4922 ROSE GOLD



NEW

4957 CHAMPAGNE



4921 BRIGHT GOLD



BRIGHT

4931 BRIGHT SILVER



4924 BRIGHT COPPER



4925 BRIGHT PINK



4926 BRIGHT RED



4927 BRIGHT BLUE



4928 BRIGHT LAVENDER



NEON

4903 NEON BLUE



4940 NEON YELLOW



4941 NEON GREEN



4942 NEON ORANGE



4944 NEON RED



4943 NEON PINK



NEW

4945 NEON DARK PINK



4987 NEON BERRY



*With non-adhesive PET-Liner | Mit nicht-klebenden PET-Liner



130°C
160°C



5 SEC
3 SEC



2,5 - 3,0 BAR



WARM
LUKE WARM



60°C
TUMBLE DRY
DRY CLEANING



MULTI LAYER



OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100
07.0.50420 HOHENSTEN MTT
Suitable for household applications
www.oeko-tex.com/standard100



500 MM X 25 M
500 MM X 10 M
1000 MM X 25 M
1524 MM X 25 M

Please find detailed information in the technical data sheet | Detaillierte Informationen entnehmen Sie dem technischen Datenblatt

#BeCreative



POLI-FLEX® TURBO
POLI-FLEX® PREMIUM
POLI-FLEX® PEARL GLITTER
TUBITHERM® FLOCK
POLI-FLEX® IMAGE
POLI-FLEX® BLOCKOUT SOFT
POLI-FLEX® NYLON
POLI-FLEX® SPORT
POLI-FLEX® STRETCH
POLI-FLEX® PRINTABLE
TURBO PRINT
ULTIMATE PRINT



HEAT TRANSFER VINYL'S 4 every challenge

TURBO PRINT 4036 MATT is the printable polyurethane transfer vinyl equipped with the same special hotmelt and features like POLI-FLEX® TURBO

TURBO PRINT 4036 MATT ist die bedruckbare Polyurethan Transferfolie mit dem selben speziellen Heißschmelzkleber und Eigenschaften wie POLI-FLEX® TURBO

130°C
5 SEC