



PL CATALYST

Product Information Bulletin

Recommended Parameters

PL CATALYST

It is a phthalate free based catalyst



Highlights

- PL Catalyst increases wash fastness.
- It creates cross-link to fabric in thermal operations under the room temperature.
- It is an auxiliary material that improved to dry-wet crocking test and wash fastness.



Usage

- Before use, please stir the product well. Do not use any additives that are not advised.
- After adding to plastisol printings paste, it should be used in 24 hours, otherwise the printing paste can be damaged.



Compliance

- It is not suitable to ecological standards because it contains PVC.



Precautions

- It is packed in 1kg, 5kg, 10kg, 20kg plastic cans.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

Recommended percentage

between 1-3%



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Health & Safety

Please see: Safety Data Sheet

