



PL Reducer

General: It is a Phthalate Free based thinner

Technical Details :

Appearance	: Liquid
Odor	: Characteristic
Color	: Transparent
Viscosity	: [(77 °F) sp: 1, rpm: 20 Brookfield] : 25 – 75 [mPa.s]
Density	: 1,0 g/cm ³ (77 °F)
pH	: N/A
Flash Point	: > 374 °F
Boiling Point	: >212°F
Solubility	: Dispersible in water

(Standards: for fastness - ISO 105-X10: 1993 / ISO 105-D01:2010 / ISO 105-B02:2013)

Advantages :

PL Reducer prevents that blocking of printings in the silk-screen.

It is easily fixed on the machine It is phthalate free.

It is used for reduce to viscosity of printings.

However, it is not suitable to ecological standards because it contains PVC.

Applications :

PL Reducer is used for reduce to viscosity of printings.

Usage :

It is advised to add (5 %) as thinner and retarder.

Packaging Information :

PL Reducer is packed in 5 kg plastic cans.

Storage & Shelf Life :

Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30) °C/(+41)-(+86)°F of temperature.



PL Reducer

TECHNICAL DATA SHEET

It should be consumed within 2 years after the production date.

Important :

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.

The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.



PL REDUCER

Product Information Bulletin

Recommended Parameters

PL REDUCER

It is a phthalate free based thinner



Highlights

- It prevents that blocking of printings in the silk screen
- It is easily fixed on the machine
- It is used for reduce to viscosity of printings.



Printing Tips

- It has been manufactured for reduce to viscosity of printings
- It is advised to add 5% as thinner and retarder



Compliance

- It is not suitable to ecological standards because it contains PVC.



Precautions

- It is packed in 1kg, 5kg, 10kg, 20kg, 25kg, 30kg and 60kg plastic cans.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

Additives

It is advised to add 5% as thinner and retarder



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Health & Safety

Please see: Safety Data Sheet

