



## FRAME ADHESIVE CT

## Product Information Bulletin

## Recommended Parameters

### FRAME ADHESIVE CT

It is used catalyzer for quick drying.



#### Highlights

- It dries much faster when compared to other adhesive.
- It is used for gluing textile materials to print frames.
- It is economical than sprays.
- It provides excellent adhesion even if high application and drying speed.



#### Printing Tips

- It has been manufactured to quick drying
- It sprays to application frames with special air spray apparatus.



#### Precautions

- Before usage, please stir the product well.
- Dispersible in water.
- It is packed in 0,8 kg plastic cans.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

#### Physical and Chemical Properties



*Appearance:* Light brown, Liquid

*Viscosity:* >100 mPas

*Density:* 1,03 g/cm<sup>3</sup>

*pH:* 2.0-4.0

*Boiling Point:* >212°F

#### Additives

It should be used with catalyzer  
(Catalyzer weight: appr. 20%)



#### Shipping & Storage

41°F - 86°F (5°C - 30°C)



#### Health & Safety

Please see: Safety Data Sheet

