



# OCTI-TECH

“innovating surfaces for custom decoration”

## SAFETY DATA SHEET

Octi-Tech Limited - Digi Coat Adhesion Promoter 250ml Bottle

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	Octi-Tech Limited - Digi Coat Adhesion Promoter 250ml Bottle
PRODUCT NO.	1813
SUPPLIER	Octi-Tech Ltd Unit 13a Provincial Park Nether Lane Ecclesfield Sheffield S35 9ZX Tel. +44 (0)114 245 44 94 (Hours 09:00 - 17:00 Mon to Fri) Fax. +44 (0)114 246 77 00 sales@octi-tech.com

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients	Conc.	CAS	EINECS	Symbols/Risk phrases
2-(2-Butoxyethoxy)ethanol (2-(2-Butoxyethoxy) ethanol)	30 - 40%	112-34-5	203-961-6	Xi; R36

### 3. HAZARDS IDENTIFICATION

Main hazards	Irritating to eyes.
--------------	---------------------

### 4. FIRST AID MEASURES

Skin contact	May cause irritation to skin. Remove contaminated clothing.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Inhalation	Irritating to respiratory system.
Ingestion	Harmful if swallowed. If swallowed, seek medical advice immediately and show this container or label.
General information	Seek medical attention if irritation or symptoms persist.

### 5. FIRE FIGHTING MEASURES

Extinguishing media	Use extinguishing media appropriate to the surrounding fire conditions.
Fire hazards	Avoid formation of dust.
Protective equipment	Wear suitable respiratory equipment when necessary.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Eliminate all sources of ignition. Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.
Environmental precautions	Advise local authorities if large spills cannot be contained. Do not allow product to enter drains.
Clean up methods	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.

## Octi-Tech Limited - Digi Coat Adhesion Promoter 250ml Bottle

## 7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Avoid sparks, flames, heat and sources of ignition. Do not breathe gas/fumes/vapour/spray.
Storage	Keep container tightly closed and in a well-ventilated place. Keep out of the reach of children.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits		
2-(2-Butoxyethoxy)ethanol	WEL 8-hr limit ppm: 10	WEL 8-hr limit mg/m <sup>3</sup> : 67.5
(2-(2-Butoxyethoxy) ethanol)	WEL 15 min limit ppm: 15	WEL 15 min limit mg/m <sup>3</sup> : 101.2
Respiratory protection	Do not breathe gas/fumes/vapour/spray. Wear suitable respiratory equipment when necessary.	
Hand protection	Chemical resistant gloves (PVC)	
Eye protection	Approved safety goggles.	

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Clear.
Odour	Characteristic.
Water solubility	Immiscible in water.

## 10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
-----------	---------------------------------

## 11. TOXICOLOGICAL INFORMATION

## 12. ECOLOGICAL INFORMATION

## 13. DISPOSAL CONSIDERATIONS

General information	Do not allow product to enter drains. Do not empty into drains.
Disposal methods	For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used. Local and national regulations.

## 14. TRANSPORT INFORMATION

ADR/RID	UN 1263 Class 3 Proper Shipping PAINT Name	Packing group II Hazard ID 33
IMDG	UN 1263 Class 3 EmS Code F-E S-E	Packing group II Marine pollutant
IATA	UN 1263 Class 3 Packing Instruction 307 (Cargo) Packing Instruction 305 (Passenger)	Packing group II Subsidiary risk - Maximum quantity 60 L Maximum quantity 5 L

## Octi-Tech Limited - Digi Coat Adhesion Promoter 250ml Bottle

## 15. REGULATORY INFORMATION

Symbols

Xi - Irritant



Risk phrases

R36 - Irritating to eyes.

Safety phrases

S1/2 - Keep locked up and out of the reach of children.

S13 - Keep away from food, drink and animal feedingstuffs.

S16 - Keep away from sources of ignition - No smoking.

S18 - Handle and open container with care.

## 16. OTHER INFORMATION

Text of risk phrases in

R36 - Irritating to eyes.

Section 2