

# VZRRNE

## TECHNICAL DATASHEET

### Face Material

Matt black embossed polymeric vinyl.

Type	Embossed polymeric vinyl	
Colour and Finish	Matt black	
Weight	194 g/m <sup>2</sup> ±10%	ISO-536
Thickness	145 µ ±10%	ISO 534-80

### Adhesive

Solvent based permanent acrylic adhesive featuring good water and cleaning agents resistance. High adhesion on a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	AP 906
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-20°C/+140°C
Shear	Very high
Tack	High N/inch <sup>2</sup>
Final Adhesion	Very high N/inch

### Liner

Type	Siliconised two side PE Kraft	
Colour and Finish	White	
Weight	140 g/m <sup>2</sup> ±10%	ISO 536
Thickness	150 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

### Applications

For decoration and lining in the Automotive industry.

### Printing Methods

As a rule it is not printed.

Testing for suitability between media, printers and inks is always recommended prior to use.

### Shelf life

36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.