



## POLI-TRANS®

300 INKJET LIGHT A4  
301 INKJET LIGHT A3

POLI-TRANS  
DESIGN YOUR OWN SHIRT

### GENERAL USE

**INKJET LIGHT** can be used in most ink jet printers. Produce high resolution transfers for application to light and pastel textiles. Transfers can be applied to cotton, polyester and poly/cotton textiles. Easy to apply giving a **soft and high quality** result.

Always single sheet feed transfer papers. Allow the ink to dry and do not apply until 10 minutes after printing.

### PRINTER SETTINGS

In general we suggest the printer settings are set to plain paper and fine or photo quality. Settings on printers vary, therefore produce a test print to determine the best settings.

### APPLICATION

Print selected image on the blank side of the transfer paper - **mirror image**. Trim around the design with scissors. Pre-heat T-shirt to remove moisture - 3 to 4 seconds.

- Press at 175 °C (350 Fahrenheit)
- Time 15 sec.
- Heavy pressure
- Remove transfer immediately (hot peel)

#### Tips

- After pressing, gently pull each side of the T-shirt, this will pull up a corner for easy release
- After the transfer has been removed, stretch the t-shirt in both directions. This helps to give a soft feel

### WASHING

- Textiles should be machine washed inside out up to 40 degrees
- Do not tumble dry, dry clean or iron directly over transfer

All information given is for guidance purposes only. Many different factors are involved in producing transfers, therefore we recommend customers to perform their own tests. These instructions are not legally binding. Information given is subject to change without notice.