

PL FOIL ADHESIVE

Product Information Bulletin

Recommended Parameters

Counts:34-55 mesh



Squeegee

Durometer: 60-80 Shore V type dr. blade



achieve an elastic, soft touching and foil covering effect in textile printing.

Highlights

If under the advised conditions is fixed, wash fastness is high

It is a phthalate free printing base used to adhesive where used to

PL FOIL ADHESIVE

- ► It is phthalate free. However, it is not suitable to ecological standards due to containing PVC.
- ► It provide easily to use during printing
- Excellent plastisol floch printings with high washing fastness.

Printing Tips

It has been manufactured for foil printing.

Compliance

It is not suitable to ecological standards due to containing PVC.

Precautions

- Never use water to reduce to viscosity.
- ► Before usage, please stir the product well. Do not use any additives that are not advised.
- After using, the silk-screen should be cleaned with water.
- Lt is provide to adhesion foil to fabric that it increases wash strenght of fabric.
- ► It is packed in 10kg cans.
- ► It can be mixed with PL pigments and PL White in any ratio.
- ► The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ► The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ► Email: info@inknovators.com

Press&Cure Temperatures

320°F(160°C) for 1.5 minutes Hand press: 320-350°F at 4-6 bar pressure in 7-10 second Continuous press:320-350°F at

4-6 bar pressure in 15-25 second



Additives

Do not use any additives that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Use water to clean



Health & Safety

Please see: Safety Data Sheet

