

PL HIGH DENSITY

Product Information Bulletin

Recommended Parameters

Counts: 24-34 mesh (High emulsion)



Squeegee

Durometer: 60-80 Shore V type dr. blade



Printing Tips

Highlights

It has been manufactured for high density effect

PL HIGH DENSITY

► It has elastic structure and high water strenght.

It is used to make for three dimension sharp line printings

It provides to elastic and soft-handfeel high density effect.

Compliance

It is not suitable to ecological standards due to containing PVC.

Precautions

► Before usage, please stir the product well. Do not use any additives that are not advised.

It is a phthalate free printing base used to achieve an elastic and soft touching effect in textile printing. It can be used as a transparent or can be coloured with pigments.

► It is phthalate free. However, it is not suitable to ecological standards due to containing PVC.

- ► After using, the screen should be cleaned with synthetic thinner or plastisol screen opener.
- ► It is packed in 10kg cans.
- ► It is used direct with PL pigments
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ► The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com





Additives

Do not use any additives that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Synthetic Thinner or Plastisol Screen Opener



Health & Safety

Please see: Safety Data Sheet

