



PL CLEAR BASE

Product Information Bulletin

Recommended Parameters

PL CLEAR BASE

It is a phthalate free printing base used to achieve an elastic, soft touching effect in textile printing



Highlights

- It is easy fixed on the machine.
- It is phthalate free. However, it is not suitable to ecological standards due to containing PVC.
- It used to improve elasticity in plastisol inks.
- Use as a base or mix it up to 20% with a plastisol inks.



Printing Tips

- It has been manufactured to improve elasticity in plastisol inks



Compliance

- It is not suitable to ecological standards due to containing PVC.




Precautions

- Before usage, please stir the product well. Do not use any additives that are not advised.
- After using, the screen should be cleaned with synthetic thinner or plastisol screen opener.
- It is packed in 10kg cans.
- It can be mixed with PL pigments and PL White in any ratio.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

Mesh

Counts: 43-120 mesh



Squeegee

Durometer: 60-80 Shore
V type dr. blade



Cure Temperatures

320°F(160°C) for 1.5 minutes



Additives

Do not use any additives
that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Synthetic Thinner or
Plastisol Screen Opener



Health & Safety

Please see: Safety Data Sheet



PL CLEAR BASE