

PL REFLECTIVE

Product Information Bulletin

Recommended Parameters

Mesh

Counts: 30-60 mesh



Squeegee

Durometer: 60-80 Shore V type dr. blade



Printing Tips

Highlights

It provides reflection to print paste.

PL REFLECTIVE

It is a phthalate free reflector pigment paste

It has been manufactured to give soft-touching effection light surface.

Cure Temperatures 320°F(160°C) for 1.5 minutes



Compliance

It is not suitable to ecological standards due to containing PVC.

Precautions

► After using, the screen should be cleaned with synthetic thinner or plastisol screen opener.

It is phthalate free. However, it is not suitable to ecological standards due to containing PVC.
 It is for reflection applications 15-20% reflective powder could be added into mixture.

- ► It is packed in 10kg cans.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ► Email: info@inknovators.com

Additives



Do not use any additives that are not advised

For Reflective Applications:

15-20% reflective powder could be added into mixture

Shipping & Storage 41°F - 86°F (5°C - 30°C)



Clean Up

Synthetic Thinner or Plastisol Screen Opener



Health & Safety

Please see: Safety Data Sheet

