

PL RED

It is a phthalate free plastisol based printing pigment base used to achieve colored printing effect with elastic covering and soft touching features in textile printing

Highlights

- ▶ Elastic and soft-handfeel plastisol colors.
- ▶ It is phthalate free. However, it is not suitable to ecological standards due to containing PVC.
- ▶ The requested color can be easily made with this product.
- ▶ It provides color productivity and elasticity on print.

Printing Tips

- ▶ It has been manufactured for plastisol colors

Compliance

- ▶ It is not suitable to ecological standards due to containing PVC.

Precautions

- ▶ Before usage, please stir the product well. Do not use any additives that are not advised.
- ▶ After using, the screen should be cleaned with synthetic thinner or plastisol screen opener.
- ▶ It is packed in 10kg cans.
- ▶ It can be mixed with PL Clear Base and PL White in any ratio.
- ▶ Fluorescent colors can be used to make alive colors.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: info@inknovators.com

Mesh

Counts: 43-120 mesh



Squeegee

Durometer: 60-80 Shore
V type dr. blade



Cure Temperatures

320°F(160°C) for 1.5 minutes



Additives

Do not use any additives that are not advised
In order to reduce the viscosity, up to 3% of PL Reducer can be added into it



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Synthetic Thinner or
Plastisol Screen Opener



Health & Safety

Please see: Safety Data Sheet

