



Product video
presentation



Join us on
Instagram




email : info@cfpflex.com

site : www.cfpflex.com

DATA SHEET

Date: 20/03/2023

PRODUCT		Printable film with SUBLIMATION INKS or INKJET for heat transfer on textiles
CODE	S701 A	box of 50 sheets A4 or A3 or in rolls
DESCRIPTION	Printable heat-adhesive film for dye sublimation inks on self-adhesive polyester carrier	
THICKNESS +/-5%	Printable film: 150 microns	Low tack adhesive polyester carrier: 120µ
TEXTILES	Cotton - Polyester - Polycotton - Nylon (to be tested before use)	
ADVANTAGES	<ul style="list-style-type: none">1. Very soft touch, thin and stretch film, can be transfered on all textiles, clear and dark2. Quick transfer at low temperature : 140°C - 15sec -Possibility to transfer with an iron3. Suitable to standard sublimation inks4. A professional quality with vibrant colours and details5. Quick and easy direct print6. Possibility to cut out the contours thanks to a plotter with an optical eye function7. No need of Application Tape as it stays flat and is easy to remove from the carrier for simple shapes8. Universal thermoadhesive with excellent proven bonding on most textiles9. Withstand many washing cycles up to 30°C .10. Ecofriendly, water-based, solvent and PVC free polyurethane.11. Low carbon profile manufacturing: all operations made under one roof12. 100% made in France, out of european raw materials.13. Last generation machines and exclusive manufacturing process	
USER'S GUIDE	<ul style="list-style-type: none">1. Parameters: With <u>Sawgrass</u>, Substrate type: Heat Transfer Vinyl (HTV) - Paper: Heat Transfer Vinyl (HTV) - Quality: High Quality With <u>Epson</u>, Paper type: DS transfert multi use/textile, Quality: high, If image is not sharp enough, go to Maintenance, Print density and reduce it up to max -30%2. You can cut out the contours with scissors or thanks to a plotter with an optical eye function Set up the blade to cut only the print film, and not the carrier, then weed.3. Put the print on textile, protect it with baking paper and press at 140°C -15 seconds (150°C-20sec for nylon). Hot Peel Note: If your visual has pre-spaced patterns, wait about 30 minutes for the ink to dry before applying Application Tape UNITAPE 503-Protect with baking paper, Press and peel cold	
WASHING TEMPERATURE	30°C	
FURTHER RECOMMENDATIONS	<ul style="list-style-type: none">1. You can put on heat press without pressing 30/60 sec to dry and fix the ink quicker2. Avoid printing significant colours' contrasts3. Wait 48 hours before washing and preferably wash separately4. Do not use bleach or other aggressive chemical agents5. Iron from inside6. Store our products in a tempered and dry room, protected from direct sun rays7. Once transfered on textile, avoid heat & UV sources (sun, heating system, tumble dryer...)	
SAFETY	Inert components, REACH compliant, without PVC, plastifiers, heavy metals, VOC, according to Oekotex Standard 100 Class 1	
RESUBLIMATION	On sublimated polyester, it is recommended to use our specific antiresublimation products	
IRON ON (A4 SHEETS)	After printing, cutting (positive mode) and weeding, protect with a baking paper, set the iron on maximum heat. Don't use any steam. Press strongly, from the center towards the edges. Warm peel	
This document is likely to be modified without notice. Please take contact with our commercial department.		