

# PT 160 G

### **Product Information**

Transparent Application Tape based on a single sided embossed Polypropylene film, with excellent flatness. It is dimensionally stable, easy to unroll, position and will not stretch or curl.

Suitable for transferring self adhesive signs, logos and lettering produced from cast or calendered CAD/CAM plotter films with matt or brilliant surface. The grey square print onto the PP film serves as positioning and cutting assistant.

Especially to be emphasised are the following properties:

- As the tape does not curl, wrinkling is avoided during lamination of large lettering. The film adjusts perfectly to the surface.
- The plasticiser resistant adhesive guarantees a strong initial tack to all types of vinyl films. The Application Tape is easily removed without leaving any residue, even after being left for a period of time.
- Excellent positioning due to the integrated square print on the PP film.
  Furthermore, the imprint serves as an optimal cutting assistant to enable accurate work.
- · Suitable for wet application.
- The film can be torn transversally, which facilitates handling.
- The embossed surface allows the film to be easily unrolled without any accumulation of electrostatic charging.

### **Technical Data**

Carrier: Polypropylene film,

Orange peel surface

Adhesive: Acrylic

Adhesion [N/cm]: 1,10 +/- 10%

Thickness [mm]: 0,11 + /-5%

#### **Standard Dimensions**

1.220 mm x 100 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17 53424 Remagen – GERMANY

Phone: +49 (0) 2642 - 9836 0 Fax: +49 (0) 2642 - 9836 37 E-Mail: info@poli-tape.de Internet: www.poli-tape.de 29/06/2018

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.