

Product video presentation



Join us on Instagram





email: info@cfpflex.com

site: www.cfpflex.com



DATA SHEET

		DATA SHEET		Date: 08/10/2021	
PRODUCT	liberty ^{Patch™} Subli BS print		•	nting with SUBLIMATION any sublimated polyester	
CODE	S901 TBS	box of 50 sheets A4 or A3 or in rolls			
	Printable Polyester TEXTILE with heat-adhesive (indirect printing with SUBLIMATION transfer				
	paper) on self-adhesive polyester carrier suitable to sublimated polyester textiles. A BLOCKSUB				
DESCRIPTION		barrier prevents resublimation			
THICKNESS +/-5%	Polyester textile: 380µ	Low tack adhesive polyester carrier: 120μ			
TEXTILES		Sublimated polyester textiles			
ADVANTAGES	 Thick and opaque textile with a FABRIC visual and touch and a total barrier to resublimation Ideal for badges, professional, sports and fashion clothes Freedom to create any badges from photos, with small letterings, with gradient, endless colors, complex patterns High Washing resistance up to 40°C A professional quality with vibrant colors Suitable to any types of sublimation inks Possibility to cut out the contours thanks to a plotter with an optical eye function, also with laser cutting Universal thermoadhesive with excellent proven bonding on most textiles Ecofriendly, water based, solvent and PVC free polyurethane, textile woven in France Low carbon profile manufacturing: all operations made under one roof 100% made in France, out of european raw materials. Last generation machines and exclusive manufacturing process 				
USER'S GUIDE WASHING	1. With a sublimation printer, print in mirror on sublimation paper with the crop marks (also in mirror) 2. Transfer your printed visual from the sublimation paper to Liberty Patch Subli with a heat press at 190°C- 50 secondes. Hot peel 3. You can cut out the contours of Liberty Patch Subli Blocksub with scissors or thanks to a plotter with an optical eye function. Set up the blade to cut only the print film, and not the carrier, then weed. 4. Then put the visual (separated from the carrier) on textile, so you can see the visual, protect it with baking paper and press at 140°C -5 seconds (adapt temperature and time according to textile) Hot Peel up to 40°C				
TEMPERATURE	up το 40 C				
1. Wait FURTHER 2. Do n RECOMMENDATIONS 3. Iron 4. Store 5. In or 6. Just resul		hours before washing. se bleach or other aggressive chemical agents. n inside. r products in a tempered and dry room, protected from direct sun rays. to prevent resublimation, it is recommended, NOT to preheat garments. r heat transfer, DO NOT stack or fold warm garments, as this could cause ation on the external side of the Flex material. onents, REACH compliant, without PVC, plastifiers, heavy metals, VOC, according			
to Oe		x Standard 100 Class 1.			
This document is likely to be modified without notice. Please take contact with our commercial department.					